

Something to get  
**CHARGED**  
up about

**Quick Charge**  
CORPORATION

**Multi Bank  
Chargers**  
MADE IN USA

*We design it, We build it, We test it for quality, We ship it with confidence*



3 Bank



6 Bank



4 Bank



10 & 12 Bank

- **Reliable:**  
Transformer based design.
- **Safe:**  
Current limited, and reverse polarity protected.  
Slow turn on with as little as 2 volts in batteries.
- **Modular Construction:**  
Field serviceable.
- **Charges all lead acid batteries:**  
Wet cell, AGM, gels. Easy to change profile  
Maintains batteries after charge to reduce sulfation.  
Can be programed for Lithium Ion too.
- **Optional temperature compensation**
- **3 year warranty**

**Some Applications:**

Battery Distributors  
Electric Vehicles  
Fleet Operators  
Warehouses  
Marine (not waterproof)

MODEL	DC VOLTS	DC AMPS	AC POWER	Dimensions H.W.D in.	WEIGHT lbs.	BATTERY CAPACITY @ 20 Hr. rate per bank
MB1210x2	12	20	117v 60hz. 3 amp	5.5 x 8 x 8	12	50-150 Amp Hour
MB1210x3	12	30	117v 60hz. 4.5 amp	5.5 x 8 x 11.75	18	50-150 Amp Hour
MB1210x4	12	40	117v 60hz. 5.5 amp	5.5 x 8 x 14	24	50-150 Amp Hour
MB1210x6	12	60	117v 60hz. 9 amp	5.5 x 8 x 21.5	36	50-150 Amp Hour
MB1210x8	12	80	117v 60hz. 10 amp	5.5 x 13.75 x 15	45	50-150 Amp Hour
MB1210x10	12	100	117v 60hz. 15 amp	5.5 x 13.75 x 21.5	61	50-150 Amp Hour
MB1210x12	12	120	117v 60hz. 17 amp	5.5 x 13.75 x 21.5	73	50-150 Amp Hour

Unlike Series or Parallel charging, the Multi Banks charge each battery independently, so batteries with different states of charge will be charged with precision. Each circuit uses a tri-color LED to indicate charge progress.



1032 S.W. 22nd St.  
Oklahoma City, OK. 73109  
ph. 800 658-2841  
fax (405) 632-5667  
e-mail: quickcharge@icnet.net  
www.quickcharge.com

All models available in 230v 50 Hz. Prefix MBXU  
Specifications are subject to change without notice